



2830

66 Block Amphenol 25 Pair

	Color	Pin	Description	Pair
LINE 1		26	T1 - Tip #1	W-BL
		1	R1 - Ring #1	BL-W
		27	A #1	W-O
		2	AG - A Lead Gnd	O-W
LINE 2		28	LG - Lamp Gnd #1	W-G
		3	L1 - Lamp #1	G-W
		29	T2 - Tip #2	W-BR
		4	R2 - Ring #2	BR-W
LINE 3		30	A #2	W-S
		5	A #9	S-W
		31	LG - Lamp Gnd #2	R-BL
		6	L2 - Lamp #2	BL-R
LINE 4		32	T3 - Tip #3	R-O
		7	R3 - Ring #3	O-R
		33	A #3	R-G
		8	A #8	G-R
LINE 5		34	LG - Lamp Gnd #3	R-BR
		9	L3 - Lamp #3	BR-R
		35	T4 - Tip #4	R-S
		10	R4 - Ring #4	S-R
LINE 6		36	A #4	BK-BL
		11	A #7	BL-BK
		37	LG - Lamp Gnd #4	BK-O
		12	L4 - Lamp #4	O-BK
LINE 7		38	T5 - Tip #5	BK-G
		13	R5 - Ring #5	G-BK
		39	A #5	BK-BR
		14	A #6	BR-BK
LINE 8		40	LG - Lamp Gnd #5	BK-S
		15	L5 - Lamp #5	S-BK
		41	T6 - Tip #6	Y-BL
		16	R6 - Ring #6	BL-Y
LINE 9		42	BL, AG, or spare (Buzzer)	Y-O
		17	SG, LK, or spare (Buzzer)	O-Y
		43	LG - Lamp Gnd #6	Y-G
		18	L6 - Lamp #6	G-Y
LINE 10		44	T7 - Tip #7	Y-BR
		19	R7 - Ring #7	BR-Y
		45	B - Ringer (Bell)	Y-S
		20	R - Ringer (Bell)	S-Y
LINE 11		46	LG - Lamp Gnd #7	V-BL
		21	L7 - Lamp #7	BL-V
		47	T8 - Tip #8	V-O
		22	R8 - Ring #8	O-V
LINE 12		48	LG - Lamp Gnd #9	V-G
		23	L9 - Lamp #9	G-V
		49	LG - Lamp Gnd #8	V-BR
		24	L8 - Lamp #8	BR-V
LINE 13		50	T9 - Tip #9	V-S
		25	R9 - Ring #9	S-V

† BREAKS NORMAL
IA2 WIRING PATTERN